

LINEAR-18 ELITE

Technical Specifications

| Voltage Range | 10-32V | | |
|---------------------------------------|--------------|--|--|
| LED Life | 50,000 Hours | | |
| Weight | 1090g | | |
| HIGH BEAM PERFORMANCE | | | |
| Total Luminous Flux | 12,150 Lm | | |
| TOTAL DRIVER 'FOV' FLUX † | 8,651 | | |
| Color Temperature | 5000K | | |
| No. of High Output LEDs | 36 | | |
| Power Consumption | 126 Watts | | |
| Peak current draw (@10V) | 12.6A | | |
| Current Draw (at 14.4V) | 8.76 Amps | | |
| CERTIFICATION | | | |
| High Beam | ECE R112 | | |
| ECE Reference | 45 | | |
| DIMENSIONS | | | |
| Width | 532mm | | |
| Depth | 62mm | | |
| Height | 40mm | | |
| PHOTOMETRIC DATA | | | |
| Horizontal/Vertical Beam Angle | 64° / 15° | | |
| 0.25Lx Line @ | 975m | | |
| 0.5Lx Line @ | 690m | | |
| 1Lx Line @ | 488m | | |
| 3Lx Line @ | 282m | | |
| · · · · · · · · · · · · · · · · · · · | - | | |