

TRIPLE-R 1250 ELITE+

Technical Specifications	White Only LED's (E-Boost / E-Mark)	Yellow Only LED's	White & Yellow LED's
Voltage Range	10-32V	10-32V	10-32V
LED Life	50,000 Hours	50,000 Hours	50,000 Hours
Weight	2400g	2400g	2400g
HIGH BEAM PERFORMANCE			
Total Luminous Flux	12,028 Lm / 2,045 Lm	9,360 Lm	21,388 Lm
Total Driver 'FOV' Flux*	7,464 Lm / 1,269 Lm	5,273 Lm	12,737 Lm
Color Temperature	5000K	PC Yellow	N/A
No. of High Output LEDs	24	20	24 White / 20 Yellow
Power Consumption	131 W / 19.6 W	92 W	243 W
Current Draw (at 14.4V)	9.1 A / 1.4 A	6.4 A	16.9 A
Peak Current Draw	12 A / 1.8 A	8.5 A	22.8 A
CERTIFICATION			
High Beam	ECE R149	N/A	N/A
ECE Reference	20		
DIMENSIONS			
Width	590mm	590mm	590mm
Depth	105mm	105mm	105mm
Height	73mm	73mm	73mm
PHOTOMETRIC DATA			
Horizontal/Vertical Beam Angle	54° / 15°	54° / 15°	54° / 15°
0.25Lx Line @	1470m / 616m	980m	1649m
0.5Lx Line @	1039m / 436m	693m	1166m
1Lx Line @	735m / 308m	490m	825m
3Lx Line @	424m / 178m	283m	476m