

TRIPLE-R 24 ELITE+

Technical Specifications	White Only LED's (E-Boost / E-Mark)	Yellow Only LED's	White & Yellow LED's
Voltage Range	10-32V	10-32V	10-32V
LED Life	50,000 Hours	50,000 Hours	50,000 Hours
Weight	4140g	4140g	4140g
HIGH BEAM PERFORMANCE			
Total Luminous Flux	24,056 Lm / 4,090 Lm	18,720 Lm	34,220 Lm
Total Driver 'FOV' Flux*	14, 928 Lm / 2,538 Lm	10,576 Lm	21,114 Lm
Color Temperature	5000K	PC Yellow	N/A
No. of High Output LEDs	48	40	48 White / 40 Yellow
Power Consumption	256 W / 37.8 W	189 W	375 W
Current Draw (at 14.4V)	17.9 A / 2.6 A	13.1 A	26.1 A
Peak Current Draw	22.7 A / 3.3 A	16.9 A	34 A
CERTIFICATION			
High Beam	ECE R149	N/A	N/A
ECE Reference	2x 20		
DIMENSIONS			
Width	1125mm	1125mm	1125mm
Depth	105mm	105mm	105mm
Height	73mm	73mm	73mm
PHOTOMETRIC DATA			
Horizontal/Vertical Beam Angle	54° / 15°	54° / 15°	54° / 15°
0.25Lx Line @	2145m / 853m	1371m	2319m
0.5Lx Line @	1517m / 603m	970m	1640m
1Lx Line @	1072m / 427m	686m	1160m
3Lx Line @	619m / 246m	396m	670m