

TRIPLE-R

THERMAL CONDUCTIVITY

maximised through CAE optimised heatsink constructed from anodised aluminium

ROAD-LEGAL CERTIFICATION

allows for electrical connection direct to the vehicle's high beam (and side light) signals.

VACUUM-METALLISED OPTICS

deliver unparalleled reflectivity for maximised light output.

OPTIONAL POSITION LIGHT FUNCTION

included across Standard products. White (Reg 7 approved) and Amber colours.

DYNAMIC DRIVE MODULATION

maintains optimal light output considering the environmental and thermal conditions of the lamp.

UNBREAKABLE POLYCARBONATE LENS

with lifetime guarantee.

VERSATILE MOUNTING SYSTEM

fully robust and able to position above or below lamp.

HIGH INTENSITY 'PREMIUM BIN' LEDS

maximise illumination levels considering power input.

FLASH TO DIM FUNCTIONALITY

to prevent glare from road signs (available on select products).

ADVANCED CORROSION RESISTANCE

enabled by in-house multi-stage pretreatment and powder coat application.

DUAL-OUTPUT TECHNOLOGY

permits operation in high or low (Reg 149 approved) output mode.

SIDE BRACKET MOUNTING

facilitated with concealed threaded point.

PREMIUM QUALITY, SATIN BLACK POWDER COAT

finish completed in-house.

OPTIONAL INTEGRATED BEACON FUNCTION

approved to UNECE Reg 65 standards.

HARDCOAT LACQUER

protects against scratches or deterioration of lens condition.

