HIGH DENSITY LEDS

Light output is maximised through use of the latest, most advanced and efficient LED technology available.



5,000 KELVIN COLOUR TEMPERATURE FOR MAXIMUM DEFINITION

While reducing fatigue and eye strain that can come from using higher colour ranges.

VACUUM-METALLISED REFLECTOR TECHNOLOGY

Designed and engineered in the UK to deliver light further and wider, in a symmetrical flood beam pattern.

RED TAIL LIGHT AND BEACON FUNCTIONS

Optional additional functionality providing enhanced safety features for commercial and industrial applications.

MALE & FEMALE DEUTSCH CONNECTORS INCLUDED

Excluding Red Tail Light + Beacon model (5 core cable) supplied with stripped bare wires.

VERSATILE MOUNTING BRACKET

Made from stainless steel and with integrated anti-rotation feature. Also available with fixed bolt for easy installation.



IP68K & IP69K PROTECTION

Tested to the toughest standards in regards water and dust ingress.

CAE OPTIMISED COOLING SYSTEM

Provides more efficient thermal management to maximise light output.

OVER VOLTAGE PROTECTION

In-built into the electronic circuitry to prevent damage, alongside protection against reverse polarity.



TILITY SERIES DUCTOR WORK LIGHT

ELECTRONIC THERMAL MANAGEMENT

Optimises light output considering the environmental and thermal conditions of the lamp.

'UNBREAKABLE' POLYCARBONATE LENS

3mm lexan polycarbonate with hardcoat lacquer provides exceptional protection from impact and environmental influences.

AUTOMOTIVE GRADE CORROSION RESISTANCE

5-stage E-coat pre-treatment prior to black powder coating ensures exceptional corrosion resistance including against harsh chemical treatments.

INTERCHANGEABLE LENS COVERS

Comprehensive range of either clear, amber, and/or diffuser lenses.

EMC PROTECTION

Approved to CISPR-25 Class 3 or Class 5, and ECE Reg10, ensuring no interference with other electrical machinery or appliances.

















LAZERLAMPS.COM