

## UTILITY-80 HD

### Technical Specifications

Voltage Range	10-32V
LED Life	50,000 Hours
Weight	1.1 kg
<b>LIGHTING PERFORMANCE</b>	
Total Luminous Flux	8940 Lm
Colour Temperature	5000K
Power Consumption	80 Watts
Peak Current Draw	6.4 Amps
Current Draw (at 14.4V)	5.6 Amps
Connector	2-Pin / 4-Pin Deutsch DT (+28cm Cable)
<b>DIMENSIONS</b>	
Width	107mm
Depth	108mm
Height	107mm
<b>CERTIFICATION &amp; STANDARDS</b>	
IP Rating #	IP68 / IP69K
EMC Standard	ECE R10
EMC Protection	CISPR-25 (Class 3)
Salt Spray Test	ISO 9227
Dump Load Protection	ISO 7637-2
<b>OPERATING CONDITIONS</b>	
Operating Temperature	-40oC ... +90oC
Vibration (BS EN 60068)	10Hz > 1000Hz, 0.14>20 (m/s <sup>2</sup> )/Hz
<b>PHOTOMETRIC DATA</b>	
Horizontal / Vertical Beam Angle	80° / 80°
1 Lux	96m
5 Lux	43m
20 Lux	21m
50 Lux *	14m

\* - 50 Lux represents HSE guidelines for effective illumination when working outdoors at night.

# - All Lazer products are designed to meet the requirements of IP68 testing. Every lamp produced at our UK facility is fully submerged under water prior to sending out.